Pol. Ind. El Salvador II
Vial D, 8
02630 La Roda
Telfn: 967 440 257
ventas@exojo.es - www.exojo.es

EXOBLACK DW 316L SERIES

Insulated double-walled modular chimney pipe, in AISI 304 and AISI 316L stainless steel, lacquered according to R.A.L. Manufactured without thermal bridge. Male-female union system with clamp included for tubes and elbows.



MATERIAL

- **Interior:** AISI 316L Stainless Steel, 0.4 mm thick.
- **Exterior:** AISI 304 Stainless Steel, 0.5 mm thick.
- **Insulation:** Rock wool with a density of 90 kg/m³ and a thickness of 25 mm.
- **Finish:** Matt black lacquer R.A.L. 9005 TXT.

FEATURES

- **Corrosion test V2:** Product suitable for use with any type of solid, liquid or gaseous fuel, having passed the condensation corrosion test.
- **Welding:** Continuous longitudinal laser on linear elements and circumferential laser welding on accessories.
- **Union system:** Male-female with union clamp included, for tubes and accessories.
- **Temperature:** Up to 600ºC.

CERTIFICATES CE

Certificate of conformity of factory production control, in compliance with the Construction Products regulation 305/2011 KIWA FPC.
Product certified by KIWA in accordance with the standard **EN1856-1:2009.**

APPLICATIONS

- Gas, diesel and non-condensing boilers.
- Solid fuel stoves, ovens.
- Commercial, industrial and sports facilities.
- Steam boilers.
- Hot air generators.
- Indoor/outdoor assembly.

DESIGNATION

- T600-N1-W-V2-L50040-G60
- T600-N1-W-V2-L50050-G60

❖ **DOP nº 8**

DIAMETERS

80/130 – 150/200 -200/250