Pol. Ind. El Salvador II
Vial D, 8
02630 La Roda
Telfn: 967 440 257
ventas@exojo.es - www.exojo.es

SERIE EXOINOX DW 304

Double-wall insulated modular chimney pipe, in AISI 304 stainless steel. Manufactured without thermal bridge. Male-female union system with clamp included for tubes and elbows.



MATERIAL

- **Interior:** AISI 304 Stainless Steel 0,5 mm thick.
- **Exterior:** AISI 304 Stainless Steel 0,5 mm thick.
- **Insulation:** Rock wool with a density of 90 kg/m³ and a thickness of 25 mm.
- **Finish:** Glossy exterior.

FEATURES

- **V2 corrosion test:** Product suitable for use with any type of solid, liquid or gaseous fuel, having passed the condensation corrosion test.
- **Welding:** Continuous longitudinal laser on linear elements and circumferential laser welding on accessories.
- **Union system:** Male-female with union collar included, for tubes and accessories.
- **Temperature:** up to 600ºC.

CERTIFICATES CE

Certificate of conformity of factory production control, in compliance with the Construction Products regulation 305/2011 KIWA FPC. Product certified by KIWA in accordance with the standard **EN1856-1:2009.**

APPLICATIONS

- Gas, diesel and non-condensing boilers.
- Solid fuel stoves, ovens.
- Commercial, industrial and sports facilities.
- Steam boilers.
- Hot air generators.
- Indoor/outdoor assembly.

DESIGNATION

- T600-N1-W-Vm-L20040-G60
- T600-N1-W-Vm-L20050-G60

❖ **DOP nº 7**

DIAMETERS

80/130 – 100/150 – 130/180 – 150/200 -200/250 – 250/300 – 300/350.